

SULLIVAN PALATEK, INC.  
 1201 US Hwy. 20 West  
 MICHIGAN CITY IN 46360  
 (219) 874-2497

## MATERIAL SAFETY DATA SHEET

### Palasyn 45

**EFFECTIVE DATE: 5/28/08**

**SUPERCEDES: 11/07/06**

#### I. PRODUCT IDENTIFICATION:

Trade Name: Palasyn 45  
 Chemical Name: Synthetic hydrocarbon, ester, & organic compound blend  
 Chemical Family: Polyalphaolefin

#### II. COMPONENTS & HAZARD STATEMENT:

**This product is non-hazardous.** The product contains no known carcinogens. No special warning labels are required under OSHA CFR 1910.1200.  
**SARA TITLE III SECTION 313 (40 CFR PART 372):** This product is not regulated under Section 313 and 40 CFR Part 372.

#### III. PHYSICAL DATA:

Viscosity: 44 cSt. @40°C  
 Specific Gravity (Water = 1.0): 0.84 – 0.87  
 Boiling Point: Not determined  
 Vapor Pressure: Negligible  
 Appearance & Odor: Straw color – bland odor  
 Solubility in Water: Negligible  
 Other Data: Non-toxic USDA H-2 approved

#### IV. FIRE & EXPLOSION HAZARD DATA:

Flash Point, ASTM D92: 450-470°F  
 Autoignition Temperature: Not Established  
 Flammability Limits: Not Established  
 Extinguishing Media: Dry Chemical; CO<sub>2</sub> Foam; Water Spray  
 Special Fire Fighting Procedure: Burning may produce irritating/noxious fumes. Firefighters should use NIOSH/MNSA approved self-contained breathing apparatus. Use water to cool fire-exposed containers to prevent pressure build-up.

#### V. REACTIVITY DATA:

Stability: This product is stable and will not react with water.  
 Materials to Avoid: Avoid strong oxidizers  
 Hazardous Decomposition Products: Carbon monoxide, Carbon dioxide

#### VI. HEALTH INFORMATION:

Eye Contact:	Flush eyes with water for 15 minutes. Call a physician if irritation develops.
Skin Contact:	Wash skin with soap and water.
Inhalation:	Remove to fresh air.
Ingestion:	First aid not normally required. If uncomfortable, call physician.

**SULLIVAN PALATEK, INC.**  
**1201 US Hwy. 20 West**  
**MICHIGAN CITY IN 46360**  
**(219) 874-2497**

**EFFECTIVE DATE: 5/28/08**

**SUPERCEDES: 11/07/06**

**PRODUCT: Palasyn 45**

**VII. HEALTH HAZARD DATA:**

Exposure Limits: Not applicable

Effects of Overexposure: Low oral and dermal toxicity. Prolonged or repeated exposure may cause irritation, nausea, and vomiting.

**VII. EMPLOYEE PROTECTION:**

For general personal hygiene, wash hands thoroughly after handling material. Avoid contact with skin and eyes.

Chemical impervious gloves are recommended for prolonged exposure.

Use in a well ventilated area

**VIII. STORAGE, SPILL & DISPOSAL PROCEDURES:**

Storage: Store in clean, dry area.

Spills: Use absorbent materials to soak up fluid.

Disposal: Dispose of this product and all associated wastes in a licensed facility in accordance with Federal, state, and local regulations. Incineration is preferred.

**IX. HAZARD RATING INFORMATION:**

	HMIS	KEY	
Health:	0	4=Severe	0=Minimal
Flammability:	1	3=Serious	
Reactivity:	O	2=Moderate	B=Gloves, Goggles
Personal Protection:	B	1=Slight	

This information contained herein is based on the data available to us and is believed to be true and accurate. Sullivan Palatek makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereof. Sullivan Palatek assumes no responsibility for injury from the use of this product.