

# Sullivan Palatek®

*Dedicated to Quality....*

*....Committed to Support*



- **SWF, Weld Flux** scalers (Cleco style) remove flux and splatter from hard surfaces.
- **SNS, Needle Scalars** (19 needles) are designed for removing paint and scale from steel and other hard or irregular surfaces and can be converted into a weld flux scaler.

**ALL**

- Standard hand throttle.
- Converts easily from one configuration to another
- Utilizes Cleco style steel
- Requires whip and oiler
- One year Warranty
- Made in USA

Specifications -SWF		
<b>Net Weight</b>	4.5 lbs	2.05 kg
<b>Length</b>	10.5 in	267 mm
<b>Bore</b>	1 in	25 mm
<b>Stroke</b>	1.125 in	28.5 mm
<b>Blows per minute</b>	4650	4650
<b>Chuck Sizes</b>	1/2 Sqr	13 mm Sqr
<b>Air Inlet (NPT)</b>	3/8 in NPT	10 mm
<b>Air Consumption*</b>	12 cfm	.34 m <sup>3</sup> /m



Specifications -SNS		
<b>Net Weight</b>	6.4 lbs	2.9 kg
<b>Length</b>	15.5 in	394 mm
<b>Bore</b>	1 in	25 mm
<b>Stroke</b>	1.125 in	28.5 mm
<b>Blows per minute</b>	4650	4650
<b>Chuck Sizes</b>	1/2 Sqr	13 mm sqr
<b>Air Inlet (NPT)</b>	3/8 in NPT	10 mm
<b>Air Consumption*</b>	12 cfm	.34 m <sup>3</sup> /m

**FOR OPTIMUM PERFORMANCE, DO NOT OPERATE TOOL ABOVE 90 PSI (6 BAR) WORKING PRESSURE.**

**WARNING:**

**ALWAYS DISCONNECT THE AIR SUPPLY BEFORE CHANGING CHISELS OR DISMANTLING THE TOOL FOR SERVICE OR REPAIR. FOR MAXIMUM SAFETY WE ADVISE THE INSTALLATION OF A SHUT-OFF VALVE AT THE END OF THE AIR LINE.**

**DO NOT EXCEED 100 PSI (7BAR) WORKING PRESSURE.**

